



Tactical Specifications

The wheeled armored personnel carrier Talaieh with unique features including very high mobility and agility , simplicity of design and ease of operation , use of semi-heavy weapon of 12.7mm and simultaneously coaxial machine gun of 7.62mm as well as firing ports on both sides of APC, is one of highly considered APCs worldwide. Lightness, high speed of deployment, and also high security of crews are of other characteristics of this type of APC. This APC is designed and manufactured based on customer's needs for deployment in counter-insurgency operations, transport of military and law enforcement forces as well as raid and surveillance operations into enemy's sites.



Engine 169 hp., 6-cylinder linear, air-cooled Gearbox 5 forward gears, 1 reverse gear Electric system 24 V Armament and ballistic protection level Main armament 12.7 mm MG, DSK Ballistic protection level resistant to 7.62mm anti-armor bullet No. of firing ports inside vehicle 7 pcs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T Power to weight ratio 16 hp./top.	POWER TRANSMISSION SYSTEM	
Electric system Armament and ballistic protection level Main armament 12.7 mm MG, DSK Ballistic protection level No. of firing ports inside vehicle 7 pcs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew Max. speed on asphalt (paved) road Gradient (on rough terrain) Side slope 30 % Height of negotiable obstacle Cruising range 800-850 km Combat weight	Engine	169 hp., 6-cylinder linear, air-cooled
Armament and ballistic protection level Main armament Ballistic protection level No. of firing ports inside vehicle Tocs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof Height to vehicle turret top 265 cm Operational specifications No. of crew Max. speed on asphalt (paved) road Gradient (on rough terrain) Side slope Height of negotiable obstacle Cruising range 800-850 km Combat weight 12.7 mm MG, DSK Read Nask Resistant to 7.62mm anti-armor bullet 7 pcs 7 pcs 642 cm 642 cm 642 cm 843 cm 644 cm 645 cm 646 cm 848 cm 67 cmising range 800-850 km 60 mbat weight	Gearbox	5 forward gears, 1 reverse gear
Main armament 12.7 mm MG, DSK Ballistic protection level resistant to 7.62mm anti-armor bullet No. of firing ports inside vehicle 7 pcs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Electric system	24 V
Ballistic protection level resistant to 7.62mm anti-armor bullet No. of firing ports inside vehicle 7 pcs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Armament and ballistic protection level	
No. of firing ports inside vehicle 7 pcs Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Main armament	12.7 mm MG, DSK
Dimensions specifications Length 642 cm Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Ballistic protection level	resistant to 7.62mm anti-armor bullet
Length Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight	No. of firing ports inside vehicle	7 pcs
Width 253 cm Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Dimensions specifications	
Height to vehicle roof 231 cm Height to vehicle turret top 265 cm Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Length	642 cm
Height to vehicle turret top Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road Gradient (on rough terrain) Side slope Height of negotiable obstacle Cruising range 800-850 km Combat weight	Width	253 cm
Operational specifications No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Height to vehicle roof	231 cm
No. of crew 2+6 Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Height to vehicle turret top	265 cm
Max. speed on asphalt (paved) road 83 km/h Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Operational specifications	
Gradient (on rough terrain) 60 % Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	No. of crew	2+6
Side slope 30 % Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Max. speed on asphalt (paved) road	83 km/h
Height of negotiable obstacle 48 cm Cruising range 800-850 km Combat weight 10.7 T	Gradient (on rough terrain)	60 %
Cruising range 800-850 km Combat weight 10.7 T	Side slope	30 %
Combat weight 10.7 T	Height of negotiable obstacle	48 cm
	Cruising range	800-850 km
Power to weight ratio 16 hp /top	Combat weight	10.7 T
101101101101101101101101101101101101101	Power to weight ratio	16 hp./ton

Optional EquipmentRun flat tire on customer request

Heating system when engine is not started on customer request