

**125 mm** 

## **GENERAL SPECIFICATIONS (HEAT - T FS, 3BK18M)**

This is SHOHADA MAHAM PARCHIN separate loading ammunition which is intended for use against armoured targets and fired with 2A46M main gun fitted to T-72 MBT. It is automatically loaded into the breach followed by a semi-combustible cartridge case. The projectile has a steel body encircled by two driving bands and its front, carries a standoff spike inside which is a piezoelectric contact sensor connected by an internal connection to a base-mounted fuze. This ammunition can penetrate 450mm of Rolled Homogenous Armour (RHA) at normal angle or 230mm at an angle of 60 deg. to the normal.

## **GENERAL SPECIFICATIONS (HE 3VOF19)**

The product is a fin stabilized and separate loading ammunition which is fired with 2A46M main gun fitted to T-72 MBT and T-80 UD. It is automatically loaded into the breach followed by a semi-combustible cartridge case. Having a muzzle velocity of 850 m/s the projectile reaches a max. range of 9400 m in the field being effective against enemy's personnel and materials by producing both fragmentation and blasts.



HE

HEAT

## **TECHNICAL SPECIFICATIONS**

Туре	HE, FS,3V0F19	HEAT - T FS, 3BK18M
Total length, fused (mm)	673	680
Total weight, fused (kg)	23.15	19
Filling material	3/1485 kg	1.600 kg Composition A4
Propellant charge (kg)	ж52	ж52-5
Cartridge case length	-	408 mm
Cartridge case weight	About 3.4 kg (w/o charges) About 10 kg (with charges)	-
Fuze	V-429E / B429E	V-15
Primer	ГҮВ-7	ГҮВ-7
Muzzle velocity (m/s)	850	905
Max. range (m)	9400	4000
Max. chamber pressure in ambient temperature (bar)	3000	3000
Armament	Tank T-72 & T-80 Gun	Tank T-72 Gun
PACKING DATA		
Туре	HE, FS,3V0F19	HEAT - T FS, 3BK18M

Туре	HE, FS,3V0F19	HEAT - T FS, 3BK18M
Quantity per Box	1 rds	1
Box Weight (kg)	52	49
Box Dim. (cm)	74 x 47 x 28	80 x 48 x 28
Box P/Pallet	8	8
Pallet Weight (kg)	About 450	About 450
Pallet Dimensions (cm)	95× 75 ×127	95 × 80 × 127